

#### **DISCLAIMER**

This document provides practicing engineers and building officials with a resource document for understanding the behavior of steel moment-frame buildings in earthquakes. It is one of the set of six State of the Art Reports containing detailed derivations and explanations of the basis for the design and evaluation recommendations prepared by the SAC Joint Venture. The recommendations and state of the art reports, developed by practicing engineers and researchers, are based on professional judgment and experience and supported by a large program of laboratory, field, and analytical research. No warranty is offered with regard to the recommendations contained herein, by the Federal Emergency Management Agency, the SAC Joint Venture, the individual joint venture partners, or the partner's directors, members or employees. These organizations and their employees do not assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any of the information, products or processes included in this publication. The reader is cautioned to review carefully the material presented herein and exercise independent judgment as to its suitability for application to specific engineering projects. This publication has been prepared by the SAC Joint Venture with funding provided by the Federal Emergency Management Agency, under contract number EMW-95-C-4770.

**Cover Art.** The beam-column connection assembly shown on the cover depicts the standard detailing used in welded, steel moment-frame construction, prior to the 1994 Northridge earthquake. This connection detail was routinely specified by designers in the period 1970-1994 and was prescribed by the *Uniform Building Code* for seismic applications during the period 1985-1994. It is no longer considered to be an acceptable design for seismic applications. Following the Northridge earthquake, it was discovered that many of these beam-column connections had experienced brittle fractures at the joints between the beam flanges and column flanges.

## State of the Art Report on Systems Performance of Steel Moment Frames Subject to Earthquake Ground Shaking

### **SAC Joint Venture**

A partnership of
Structural Engineers Association of California (SEAOC)
Applied Technology Council (ATC)
California Universities for Research in Earthquake Engineering (CUREe)

# Prepared for the SAC Joint Venture Partnership by Helmut Krawinkler

Department of Civil Engineering, Stanford University

#### **Project Oversight Committee**

William J. Hall, Chair

Shirin Ader	James R. Harris
John M. Barsom	Richard Holguin
Roger Ferch	Nestor Iwankiw
Theodore V. Galambos	Roy G. Johnston
John Gross	Len Joseph

Duane K. Miller John Theiss John H. Wiggins

#### **SAC Project Management Committee**

SEAOC: William T. Holmes	Program Manager: Stephen A. Mahin
ATC: Christoper Rojahn	Project Director for Topical Investigations:
CUREe: Robin Shepherd	James O. Malley
-	Project Director for Product Development:
	Ronald O. Hamburger

#### **Topical Investigation Team**

C. Allin Cornell	Gregroy McRae	Andre Reinhorn
Kazukhio Kazai	Farzad Naeim	Paul Sommerville
Bruce Maisson		

#### **Technical Advisory Panel**

Jacques Cattan	Dennis Randall	W. Lee Shoemaker
Gary C. Hart	Arthur E. Ross	John Theiss
Y. Henry Huang	C. Mark Saunders	

#### **SAC Joint Venture**

SEAOC: www.seaoc.org ATC: www.atcouncil.org CUREe: www.curee.org

September 2000

#### THE SAC JOINT VENTURE

SAC is a joint venture of the Structural Engineers Association of California (SEAOC), the Applied Technology Council (ATC), and California Universities for Research in Earthquake Engineering (CUREe), formed specifically to address both immediate and long-term needs related to solving performance problems with welded, steel moment-frame connections discovered following the 1994 Northridge earthquake. SEAOC is a professional organization composed of more than 3,000 practicing structural engineers in California. The volunteer efforts of SEAOC's members on various technical committees have been instrumental in the development of the earthquake design provisions contained in the Uniform Building Code and the 1997 National Earthquake Hazards Reduction Program (NEHRP) Recommended Provisions for Seismic Regulations for New Buildings and other Structures. ATC is a nonprofit corporation founded to develop structural engineering resources and applications to mitigate the effects of natural and other hazards on the built environment. Since its inception in the early 1970s, ATC has developed the technical basis for the current model national seismic design codes for buildings; the de facto national standard for postearthquake safety evaluation of buildings; nationally applicable guidelines and procedures for the identification, evaluation, and rehabilitation of seismically hazardous buildings; and other widely used procedures and data to improve structural engineering practice. CUREe is a nonprofit organization formed to promote and conduct research and educational activities related to earthquake hazard mitigation. CUREe's eight institutional members are the California Institute of Technology, Stanford University, the University of California at Berkeley, the University of California at Davis, the University of California at Irvine, the University of California at Los Angeles, the University of California at San Diego, and the University of Southern California. These laboratory, library, computer and faculty resources are among the most extensive in the United States. The SAC Joint Venture allows these three organizations to combine their extensive and unique resources, augmented by subcontractor universities and organizations from across the nation, into an integrated team of practitioners and researchers, uniquely qualified to solve problems related to the seismic performance of steel moment-frame buildings.

#### **ACKNOWLEDGEMENTS**

Funding for Phases I and II of the SAC Steel Program to Reduce the Earthquake Hazards of Steel Moment-Frame Structures was principally provided by the Federal Emergency Management Agency, with ten percent of the Phase I program funded by the State of California, Office of Emergency Services. Substantial additional support, in the form of donated materials, services, and data has been provided by a number of individual consulting engineers, inspectors, researchers, fabricators, materials suppliers and industry groups. Special efforts have been made to maintain a liaison with the engineering profession, researchers, the steel industry, fabricators, code-writing organizations and model code groups, building officials, insurance and risk-management groups, and federal and state agencies active in earthquake hazard mitigation efforts. SAC wishes to acknowledge the support and participation of each of the above groups, organizations and individuals. In particular, we wish to acknowledge the contributions provided by the American Institute of Steel Construction, the Lincoln Electric Company, the National Institute of Standards and Technology, the National Science Foundation, and the Structural Shape Producers Council. SAC also takes this opportunity to acknowledge the efforts of the project participants – the managers, investigators, writers, and editorial and production staff – whose work has contributed to the development of these documents. Finally, SAC extends special acknowledgement to Mr. Michael Mahoney, FEMA Project Officer, and Dr. Robert Hanson, FEMA Technical Advisor, for their continued support and contribution to the success of this effort.

## **TABLE OF CONTENTS**

LI	ST OF FIG	URES	ix
LI	ST OF TAI	BLES	xix
1.	INTROD	UCTION	1-1
	1.1	Purpose	1_1
	1.2	Background	1-2
	1.3	Objectives	
	1.4	Historical Perspective	
2	INELAST	TIC CYCLIC CHARACTERISTICS OF STRUCTURAL ELEMENTS	2-1
	2.1	Beam Behavior.	
	2.2	Column Behavior	
	2.3	Panel Zone Shear Behavior.	
	2.4	Connection Behavior	
3	METHOL	OS FOR PREDICTION OF SEISMIC DEMANDS	3-1
٥.	3.1	Modeling of Structural Elements for Inelastic Analysis	
	0.1	3.1.1 Modeling of Post-Fracture Behavior at Welded Connections	
		3.1.2 Modeling of Beams with Post-Northridge Connections	
		3.1.3 Modeling of Panel Zone Shear Behavior	
		3.1.4 Modeling of Gravity Loads for P-Delta Effects	
		3.1.5 Other Modeling Considerations	
	3.2	Inelastic Time History Analysis	3-11
	3.3	Inelastic Static Analysis (Pushover Analysis)	3-12
	3.4	Elastic Methods of Analysis	
		3.4.1 Elastic Static Analysis	
		3.4.2 Elastic Dynamic Analysis	3-14
	3.5	Building Structures, Analytical Models, and Ground Motions Used in the	
		SAC System Performance Studies	
		3.5.1 Two-Dimensional Models	
		3.5.2 Three-Dimensional Models	3-18
4.		ED ISSUES AFFECTING THE SEISMIC PERFORMANCE OF WSMF	
		URES	
	4.1	Global and Local Performance Issues	
	4.2	Importance of Relative Strength of Elements at a Connection	
		4.2.1 The Strong Column Concept	
		4.2.2 Panel Zone Shear Strength	4-3
	4.2	4.2.3 Sensitivity of Prediction of Local Demands	
	4.3	Effects of Relative Member Strength on Local Deformation Demands	
	4.4	Structure P-Delta Effect and Dynamic Instability	
		4.4.1 The P-Delta Problem	
		447 Case Singy 1: The SAC 70-Slory LOS Angeles Billiong	4-1/

		4.4.3	Case Stu	dy 2: The SAC 3-Story Seattle Building	4-25
		4.4.4		y Assessment of Importance of P-Delta Effects	
5.	INIEL ACT	IC CEI	SMIC DE	MANDS FOR DUCTILE WSMF SYSTEMS WITH FULLY	
۶.				TIONS	
	5.1			1013	
	3.1	5.1.1		s of this Chapter	
		5.1.1		Motion Issues	
	5.2			al Behavior – Pushover Analysis	
	3.2	5.2.1		Lateral Load - Drift Behavior	
		3.2.1	5.2.1.1	Variation in Story Drift Over Height	
			5.2.1.2	Overstrength	
			5.2.1.3	Effects of Weak Panel Zones	5-11
			5.2.1.4	Strength of Structures in Regions of Different Seismicity	
			5.2.1.5	Effects of Subjective Design Decisions	
			5.2.1.6	Post-Northridge Structures	
			5.2.1.7	Sensitivity to Analytical Model	
			5.2.1.8	Contributions of Gravity Frames	
			5.2.1.9	Expected Seismic Performance Based on Pushover Analysis	5-13
		5.2.2		ement Behavior	
		0.2.2	5.2.2.1	Evaluation of Relative Member Strength	
			5.2.2.2	Beam Plastic Rotations for Strong Panel Zones	
			5.2.2.3	Panel Zone Plastic Distortions for Weak Panel Zones	
			5.2.2.4	Sharing of Plastic Deformations Between Beams and Panel	
				Zones	5-18
			5.2.2.5	Effects of Subjective Design Decisions	
			5.2.2.6	Effect of Nominal versus Expected Material Yield Strength	
			5.2.2.7	Post-Northridge Connections	
			5.2.2.8	Effect of Gravity Frames	
			5.2.2.9	Dispelling a Myth	
	5.3	Roof a	and Story	Drift Demands Under Ground Motions of Different	
					5-24
		5.3.1		Characteristics of Sets of Records Used in Baseline Study	
		5.3.2	Roof Dr	ift Demands	5-28
		5.3.3	Story Dr	ift Demands	5-29
			5.3.3.1	Observations Based on Response of SAC Structures	5-31
			5.3.3.2	Distribution of Story Drifts Over Height	
			5.3.3.3	Ratio of Maximum Story Drift to Roof Drift	5-35
			5.3.3.4	Effects of P-Delta on Story Drifts	5-37
			5.3.3.5	Sensitivity of Story Drifts to Design Issues	5-38
			5.3.3.6	Sensitivity of Story Drifts to the Relative Strength of Beams	
				vs. Panel Zones	
			5.3.3.7	Dispersion of Story Drift Demands	5-40
			5.3.3.8	Outliers in Drift Demands	
			5.3.3.9	Residual Story Drift	5-41
			5.3.3.10	Post Northridge Structures	5-42

	5.3.3.11 Effect of Modeling Accuracy on Story Drift Predictions	5-45
	5.3.3.12 Drift Hazard Curves	
5.4	Global Force Demands	
	5.4.1 Base and Story Shear Forces	
	5.4.2 Base and Story Overturning Moments	5-53
5.5	Demands for Columns	
	5.5.1 Column Moment and Plastic Rotation Demands	
	5.5.2 Column Plastic Rotation Demands at Base of First-Story Column	5-61
	5.5.3 Column Axial Forces	5-62
	5.5.4 Moment and Axial Force Demands at Column Splices	5-64
5.6	Demands for Beam Plastic Rotations and Panel Zone Distortions	5-67
5.7	Sensitivity of Response	5-68
	5.7.1 Effect of Strain-Hardening	
	5.7.2 Effect of Damping	
	5.7.3 Effect of Period Variability	
	5.7.4 Effect of Material Strength Variability	
	5.7.5 Effect of Configuration and Redundancy	
5.8	Effects of Ground Motion Characteristics	
	5.8.1 Near-Fault Effects	
	5.8.1.1 SAC Near-Fault Study	
	5.8.2 Soft Soil Effects	
	5.8.2.1 SAC Pilot Study on Soft Soil Effects	
5.9	3-D Effects	
0.5	5.9.1 Simultaneous Horizontal Components of Motion	
	5.9.1.1 Behavior Difference of 3-D and 2-D Frames	
	5.9.1.2 Effect of Shaking Direction on Drift Magnitude	
	5.9.1.3 Assessing Bi-Axial Demand in Inelastically Behaving 3	
	Frames	
	5.9.1.4 M <sub>x</sub> -M <sub>y</sub> -P Interaction	
	5.9.1.5 Summary	
	5.9.2 Vertical Component of Motion	
	5.9.2.1 Estimation of Peak Axial Force Due to Vertical Shaking	
5.10	Post-Northridge Structures	
5.10	5.10.1 Structures with Cover Plate Connections	
	5.10.2 Reduced Beam Sections	
5.11	Effects of Hysteretic Characteristics on Seismic Demands	
3.11	5.11.1 Effects of Hysteretic Characteristics on Seismic Demands for SA	
	Structures	
	5.11.2 Summary Assessment of the Effects of Hysteretic Characteristics	
	Seismic Demands	
5 10		
5.12	Special Issues	
	5.12.1 Approximate Prediction of Demands for WSMF Structures	
	5.12.1.1 Estimation of Roof Drift Demands	3-111
	5.12.1.2 Estimation of Inelastic Roof Drift Demand Without P-Delta Effects	5_113
	WITHOUT P-LIEITS HTTACTS	7-113

			5.12.1.3 Estimate of Effects of P-Delta on Inelastic	
			Roof Drift Demand	5-115
			5.12.1.4 Relationship Between Roof Drift and Story Drift	5-116
			5.12.1.4.1 Estimation of the Ratio of Maximum Story	
			Drift to Roof Drift	5-116
			5.12.1.4.2 Variation of the Ratio of Story Drift to Roof	
			Drift Over Height of Structure	5-116
		5.12.2	Value of Pushover Analysis	
			v	
6.	BEHAVI	OR OF	FRAMES WITH PRE-NORTHRIDGE CONNECTIONS	6-1
	6.1		uction	
	6.2		tical Modeling of Fractured Connections	
			Beam Flange Fractures	
			Column Fractures	
	6.3		s of Beam Flange Connection Fractures on Drift Demands	
		6.3.1	Approach	
			6.3.1.1 Approach for Sensitivity Studies	
		6.3.2	Beam Bottom Flange Connection Fractures Only (BFO Cases)	
			6.3.2.1 Brittle Base Case Results for LA 9-Story Structures	
			6.3.2.1.1 $\theta_{\text{max}}$ and $\theta_{\text{ave}}$ Statistics	
			6.3.2.1.2 Spatial Variations of $\theta_i$ Statistics	
			6.3.2.2 Brittle Base Case Results for All Structures	
			6.3.2.2.1 $\theta_{\text{max}}$ and $\theta_{\text{ave}}$ Statistics	
			6.3.2.2.2 Extremes and Collapses	
			6.3.2.2.3 Summary of Brittle Base Case Results	
			6.3.2.3 Results of Sensitivity Studies	
			6.3.2.3.1 Sensitivity to Early Fractures	
			6.3.2.3.2 Sensitivity to Plastic Rotation Capacity, $\theta_{f+}$	
			6.3.2.3.3 Sensitivity to Residual Moment Strength, $M_{\text{red}}$	
			6.3.2.3.4 Summary of Results of Sensitivity Studies	
		6.3.3	Beam Top and Bottom Flange Connection Fractures (TBF Cases)	
		0.5.5	6.3.3.1 TBF Connection Fracture Results for LA 9-Story Structure	
			· ·	
			6.3.3.1.1 $\theta_{max}$ Statistics	0-13 6 16
			<u> </u>	
			6.3.3.1.3 Spatial Variations of $\theta_i$ Statistics	
			6.3.3.2 TBF Connection Fracture Results for All Structures	
		621	6.3.3.3 Summary of TBF Connection Fracture Results	
		6.3.4	Conclusions on Effects of Beam Flange Connection Fractures	
		6.3.5	Effects of Interior Frames; The M1+ Model	
			6.3.5.1 Collapses	
		626	6.3.5.2 Story Drifts	
		6.3.6	Effects of Near-Fault Records	
			6.3.6.1 Maximum Story Drift Angle Results	
		627	6.3.6.2 Conclusions Based on LA 9-Story Structure	
		D.3./	Effects of Redundancy	n-25

		6.3.7.1 Modeling Assumptions	
		6.3.7.2 Story Drift Results	6-27
	6.4	Effects of Column Fractures on Drift Demands	
		6.4.1 Bottom Flange Fractures Only	
		6.4.2 Top and Bottom Flange Fractures	
		6.4.3 "Pattern" of Column Fracture Triggers in Lower Stories	
		6.4.4 Conclusions Based on LA 9-Story	6-32
	6.5	Methodology for Evaluation of Effects of Connection Fractures in a	
		Probabilistic Format	
		6.5.1 Procedure for Computing Drift Hazard Curves	
		6.5.1.1 Spectral Acceleration Hazard	
		6.5.1.2 Relationship between Spectral Acceleration and Drift	
		6.5.1.3 Drift Demand Hazard	
		6.5.2 Numerical Example	
	6.6	Methodology for Safety Evaluation of Structures	
		6.6.1 Collapse Limit State Probability	
		6.6.2 Incremental Dynamic Analyses (IDAs)	
		6.6.3 Numerical Example	6-42
7. FF	RAMES	WITH PARTIALLY RESTRAINED CONNECTIONS	7-1
	7.1	Modeling of Strength and Stiffness Properties of PR Connections	7-1
	7.2	Seismic Demands for Frames with PR Connections	
		7.2.1 SAC Case Studies of Frames with PR Connections	7-5
		7.2.2 Global Behavior Obtained from Pushover Analysis	7-6
		7.2.3 Story Drift Demands	
		7.2.4 Connection Rotation Demands	
	7.3	Summary Observations on Frames with PR Connections	7-16
8 SI	IMMA	RY AND CONCLUSIONS	8-1
	8.1	Analytical Modeling	
	8.2	Element Behavior Issues	
	8.3	System Behavior Issues	
	8.4	Global Strength Issues	
	8.5	Effects of Ground Motion Characteristics	
	8.6	Effects of Connection Fractures on Response and Safety	
	8.7	Behavior of Frames with PR Connections	
APPF	NDIX .	A – SAC GROUND MOTIONS	Δ_1
1	A.1	Description of Sets of Ground Motions	
	A.2	Spectral Characteristics of Ground Motions	A-1
		~ r	

<b>APPEN</b>	DIX B – THE SAC MODEL BUILDINGS	B-1
B.1	Description of Buildings and Basic Loading Conditions	B-1
	Los Angeles (LA) Structures	
	Seattle (SE) Structures	
	Boston (BO) Structures	
B.5	Redesigned LA 9-Story Structures	B-6
REFERI	ENCES, FEMA REPORTS, SAC REPORTS, AND ACRONYMS	R-1
SAC PH	IASE II PROJECT PARTICIPANTS	S-1